



<https://wearwell.com/>

24/SEVEN® LockSafe® MAX Diamond-Plate-GR

Group 583-GR

24/SEVEN® LockSafe® MAX **combines the benefits of a modular product with all the comfort of an anti-fatigue mat.** Each 3 ft x 3 ft (91cm x 91cm) tile features secure, seamless connections on all sides. The **resilient, long-lasting EVA foam sponge base** makes 24/SEVEN® LockSafe® MAX the ultimate solution for prolonged standing in areas big and small.

The male and female connectors feature a flange that **lock together and won't come apart until you want them to.** Traditional modular rubber mats have passive connections that fail, leaving dangerous, unsightly trip hazards. 24/Seven MAX saves the time and labor of continual assembly and potential workers' comp claims.

Choose 24/SEVEN® LockSafe® MAX for a dependable, safe, ergonomic floor.

- Diamond-Plate surface pattern
- Large 3 ft x 3 ft tiles (91cm x 91cm)
- Grease Resistant Rubber
- Also available with a [smooth, lightly texture](#) surface
- U.S. PATENT No. D882,293 S; 10,914,081; 11,174,648; 11,454,037

Categories & Applications Anti-Fatigue Flooring

Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner.
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	GR/Natural Rubber and EVA Foam
Recycled	25%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'B'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .54 / Wet COF = .45
Compression Deflection	ASTM D575 - 16.5psi @ 25% =.16" distance compressed
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
583.1x3x3GRBK	715411014392	Black	1 In. (25 mm)	3' x 3'	Y	EA