



<https://wearwell.com/>

ErgoDeck General Purpose Solid - Modular Ergonomic Interlocking Floor Tiles

Group 566

A comfortable, ergonomic floor that will withstand heavy use. The [LockSafe Positive Interlocking System](#) delivers secure connections. Perfect for [lean manufacturing](#), tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck General Purpose addresses worker health and comfort in areas with primarily foot traffic and light cart traffic.

- U.S. PATENT NO. D502,557; D520,650
- Softer compound for greater standing relief in wet or dry applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and [Drainage](#) version and with GRITSHIELD for extra traction
- Overall thickness 7/8"

Learn more about ErgoDeck ergonomic flooring [here](#).

Categories & Applications Anti-Fatigue Flooring

Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Wet Area, Oily
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC
Recycled	>80%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .65 / Wet: COF = .42
Compression Deflection	ASTM D575-91 /14.15%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
566.78x18x18BK-CS10	715411698387	Black	7/8 In. (22 mm)	18" x 18"	Y	CS-10
566.78x18x18CH-CS10	715411787210	Charcoal	7/8 In. (22 mm)	18" x 18"	Y	CS-10

