



<https://wearwell.com/>

WorkRite

Group 474

A popular and economical general-purpose drainage mat. WorkRite is ideal for wet commercial or industrial areas.

- Can be used in food and beverage processing and production environments
- Lightweight design for frequent cleanings
- Natural Rubber
- Molded-in safety edges
- Suitable for areas with water and non-caustic liquid agents
- Overall thickness 1/2" (13 mm)

Categories & Applications Anti-Fatigue Matting

Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Wet Area, Oily, Slippery, Wet/ Dry
Customization Options	Standard Sizes Only
Solid or Drainage	Drainage
Material	Grease Resistant Natural Rubber
Recycled	>33%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Not Available
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = > .90 / Wet: COF = .34
Compression Deflection	ASTM D575 - 17.9psi @ 25% =.14" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
474.12x3x10BK	715411305414	Black	1/2 In. (13 mm)	3' x 10'	Y	EA
474.12x3x20BK	715411305445	Black	1/2 In. (13 mm)	3' x 20'	Y	EA
474.12x3x5BK	715411305506	Black	1/2 In. (13 mm)	3' x 5'	Y	EA