



<https://wearwell.com/>

Autoclavable Mat

Group 580

Autoclavable Mat is the standing product of choice in sterile environments such as hospital OR, surgery centers, laboratories, pharmaceuticals, and life sciences. The rubber surface domes-flexible and resilient underfoot provide long lasting relief for long shifts and extended standing. Featuring a 100% latex-free, non-porous rubber that does not promote microbial growth, Autoclavable Mat promotes health & wellness for professionals working in sterile applications.

- USP 797 compliant after autoclaved
- Latex-Free, non-porous rubber compound
- 100% nitrile rubber
- Tested at 52 autoclave cycles - 120 degrees C @15 psi for 20 minutes with no deformation
- Overall thickness 1/2"

Categories & Applications Anti-Fatigue Matting

Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Wet Area, Oily
Customization Options	Standard Sizes Only
Solid or Drainage	Solid
Material	Grease Proof Nitrile Rubber
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	Tested at 52 autoclave cycles - 120 degrees C @15 psi for 20 minutes with no deformation
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet: COF = .68
Compression Deflection	ASTM D575 - 9.3 psi @ 25% =.25" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
580.12x2x3GY	715411011643	Gray	1/2 In. (13 mm)	2' x 3'	Y	EA